

# Android Mobile Computers



	EA520	EA630+	PA760	HT730	HT330	WD200
<b>OS</b>	Android 11	Android 11	Android 10	Android 10	Android 12	Android 10
<b>CPU</b>	2GHz Octa-Core	2GHz Qualcomm® Snapdragon™ 662 Octa-Core 64-bit	2.2GHz Qualcomm Snapdragon™ 660 Octa-Core 64 bit	2.3GHz Qualcomm 720G (SM7125) Octa-Core	2 GHz Octa-Core	2.2 GHz Qualcomm Snapdragon™ 660 Octa-Core, 64bits
<b>Display</b>	5in TFT LCD HD Gorilla® Glass 3 (720x1280) Color Screen	Capacitive type 5 point multi-touch 6in Gorilla® Glass 6 18:9 Full HD (2160x1080) 450nits Backlight	5.45in Gorilla Glass III TouchScreen	4in TFT-LCD WVGA (480x800) Capacitive Touch Screen Compatible with Gloves, Wet Hands	4in WVGA (800x480) 450nits Backlight Compatible with Gloves, Wet Hands	3.1in TFT-LCD (800x480) 450nits Backlight Compatible with Gloves, Wet Hands
<b>Memory</b>	4GB RAM / 64GB Flash	4GB RAM / 64GB Flash	4GB RAM / 64GB Flash	4GB RAM / 64GB Flash	3GB RAM / 32GB Flash	3 GB RAM / 32 GB Flash
<b>Wireless Communication</b>	Bluetooth® 5 WLAN 2.4G and 5GHz WWAN 4G LTE GPS	Bluetooth® 5 WLAN 2.4GHz and 5GHz WWAN GPS	Bluetooth® 5 WLAN 2.4GHz WWAN 4G LTE and Dual SIM GPS	Bluetooth® 5 WLAN 2.4GHz WWAN 4G LTE and Dual SIM GPS	Bluetooth® 5 WLAN 2.4GHz and 5GHz WWAN 4G LTE and Dual SIM GPS	Bluetooth® 5 WLAN IPv4, IPv6 WWAN 4G LTE
<b>Expansion</b>	Micro SD up to 256GB	Micro SD up to 256GB	Micro SD up to 128GB	Micro SD up to 256GB	Micro SD up to 256GB	Nano SIM Slot
<b>Scanner</b>	1D / 2D Imager	1D / 2D Imager	1D CCD / 2D Imager	1D / 2D Imager	1D / 2D Imager	-
<b>RFID</b>	HF / NFC	HF / NFC	NFC	HF / NFC	HF / NFC and UHF optional	HF / NFC
<b>Keypad</b>	-	-	-	28- or 32-key with backlight + Touchscreen	32-key with backlight + Touchscreen	Touchscreen
<b>Gun Grip Option</b>	Gun Grip and Wrist Mount	Standard or RFID Gun Grip	Standard or RFID Gun Grip	Standard or RFID Gun Grip	Standard Gun Grip	-
<b>Battery</b>	3.8V 4100mAh Li-ion battery Removable	3.85V 4000mAh Li-ion battery	3.7V Li-Ion 4000mAh	3.7V 6700mAh 1-Minute Hot Swap	3.85V Li-Ion 5200mAh Removable	3.85V Li-Polymer 2050mAh (Embedded)
<b>IP Rating</b>	IP67	IP65	IP67	IP67	IP67	IP67
<b>Dimensions</b>	6in H x 3in W x 0.5in D	6.1in H x 3in W x 0.5in D	6.4in H x 2.9in W x 0.6in D	7.6in H x 2.8in W x 1.3in D	7in H x 2.7in W x 0.9in D	3.8in H x 2.3in W x 0.5 D
<b>Weight</b>	8.5 oz.	8.11 oz.	10.5 oz.	13.9 oz.	10 oz.	3.8 oz.
<b>Drop Spec.</b>	5ft	5ft	6ft	6ft	5ft	5ft
<b>Cradles</b>	USB	USB, Ethernet, Single Slot and 4-Slot	USB, Ethernet, Single Slot and 4-Slot	USB, Ethernet, Single Slot and 4-Slot	Single Slot USB	USB, 4 Bay

# Long Range Android Mobile Computer + Gun Grips

	HT730 Long-Range	PA760 Long Range Gun Grip
<b>OS</b>	Android 10	Android 10
<b>CPU</b>	2.3GHz Qualcomm 720G (SM7125) Octa-Core	2.2GHz Qualcomm Snapdragon™ 660 Octa-Core 64 bit
<b>Display</b>	4in TFT-LCD WVGA (480x800) Capacitive Touch Screen Compatible with Gloves, Wet Hands	5.45in Gorilla Glass III TouchScreen
<b>Memory</b>	4GB RAM / 64GB Flash	4GB RAM / 64GB Flash
<b>Wireless Communication</b>	Bluetooth® 5 WLAN 2.4GHz WWAN 4G LTE and Dual SIM GPS	Bluetooth® 5 WLAN 2.4GHz WWAN 4G LTE and Dual SIM GPS
<b>Expansion</b>	Micro SD up to 256GB	Micro SD up to 128GB
<b>Scanner</b>	1D / 2D Imager 65ft Scan Range	1D CCD / 2D Imager
<b>RFID</b>	NFC	NFC
<b>Keypad</b>	28- or 32-key with backlight + Touchscreen	-
<b>Gun Grip Optional</b>	Standard or RFID Gun Grip	Standard or RFID Gun Grip
<b>Battery</b>	3.7V 6700mAh 1-Minute Hot Swap	3.7V Li-Ion 4000mAh
<b>IP Rating</b>	IP67	IP67
<b>Dimensions</b>	7.6in H x 2.8in W x 1.3in D	6.4in H x 2.9in W x 0.6in D
<b>Weight</b>	13.9 oz.	10.5 oz.
<b>Drop Spec.</b>	6ft	6ft
<b>Cradles</b>	USB, Ethernet, Single Slot and 4-Slot	USB, Ethernet, Single Slot and 4-Slot

# UHF RFID Readers



	RP902	RG630 (EA630+ UHF)	HT730 UHF	RG760 (PA760 UHF)
<b>OS</b>	-	Android 11	Android 10	Android 10
<b>CPU</b>	-	2GHz Qualcomm® Snapdragon™ 662 Octa-Core 64-bit	2.3GHz Qualcomm 720G (SM7125) Octa-Core	2.2GHz Qualcomm Snapdragon™ 660 Octa-Core 64 bit
<b>Display</b>	0.96in	Capacitive type 5 point multi-touch 6in Gorilla® Glass 6 18:9 Full HD (2160x1080) 450nits Backlight	4in TFT-LCD WVGA (480x800) Capacitive Touch Screen Compatible with Gloves, Wet Hands	5.45in Gorilla Glass III TouchScreen
<b>Memory</b>	-	4GB RAM / 64GB Flash	4GB RAM / 64GB Flash	4GB RAM / 64GB Flash
<b>Wireless Communication</b>	Bluetooth® 5	Bluetooth® 5 WLAN 2.4GHz and 5GHz WWAN GPS	Bluetooth® 5 WLAN 2.4GHz WWAN 4G LTE and Dual SIM GPS	Bluetooth® 5 WLAN 2.4GHz WWAN 4G LTE and Dual SIM GPS
<b>Expansion</b>	-	Micro SD up to 256GB	Micro SD up to 256GB	Micro SD up to 128GB
<b>Scan Performance</b>	Read Distance: 6.5ft 27dBm RF Power (Adjustable)	Read Distance: 26ft (Circular Antenna) Tag Read Rate: 750 tags/sec	Read Distance: 50ft (Circular Antenna) Tag Read Rate: 750 tags/sec	Read Distance: 20ft (Circular Antenna) Tag Read Rate: 750 tags/sec
<b>RFID</b>	UHF Linearly Polarized Antenna	UHF / NFC RFID Engine : M6e-Micro (RAIN RFID supported)	UHF / NFC RFID Chip: IMPINJ R2000	UHF / NFC RFID Engine : M6e-Micro (RAIN RFID supported)
<b>Keypad</b>	3 Buttons: Trigger, Function, Select	Trigger	28- or 32-key with backlight + Touchscreen, Trigger	Trigger
<b>Gun Grip Optional</b>	-	Yes	Yes	Yes
<b>Battery</b>	3.7V Li-Ion 1100mAh (Changeable)	3.85V 4000mAh Li-ion battery	3.7V 6700mAH 1-Minute Hot Swap	3.7V Li-Ion 4000mAh
<b>IP Rating</b>	IP65	IP52	IP65	IP52
<b>Dimensions</b>	4.3in H x 2in W x 1.1in D	6in H x 3in W x 6in D	8in H x 3.2in W x 6.5in D	5.7in H x 2.9in W x 6.2in D
<b>Weight</b>	3.7 oz.	9.7 oz. (without terminal)	26.5 oz.	9.5 oz. (without terminal)
<b>Drop Spec.</b>	4ft	4ft	6ft	6ft
<b>Cradles</b>	Single Slot Charging with Spare Battery Slot	USB, Ethernet, Single Slot and 4-Slot	USB, Ethernet, Single Slot and 4-Slot	USB, Ethernet, Single Slot and 4-Slot

\*The Unitech Protection Plus Warranty Program covers all system devices for a minimum of one year and all cables and batteries for 90 days. Additional prepaid services, such as Extended and Comprehensive Warranty offer coverage for an additional one or two year term.

# Rugged Tablets

	TB85+	TB110	TB162
<b>OS</b>	Android 10	Windows 10 IOT	Windows 10
<b>CPU</b>	2.2 GHz Qualcomm MSM8953 PRO Octa-Core	1.92GHz Quad-Core	2.4 GHz Quad-Core
<b>Display</b>	8" 1280 x 800 LCD Display 450nits Brightness	10.1" 1280 x 800	10.1" 1900 x 1200 pixels
<b>Memory</b>	4GB RAM / 64 GB Flash MicroSD slot	4GB RAM / 64GB Flash	128 GB ROM / 8 GB RAM
<b>Frequency</b>	13.56MHz	-	13.56MHz
<b>Reading Distance</b>	Contact	Contact	
<b>Tag Support</b>	ISO14443A/B, ISO15693 standard	-	ISO14443A/B, ISO15693 standard
<b>Other Data Collection</b>	1D or 2D Imager (Optional), Camera, MSR Reader	1D or 2D Imager, Camera	1D or 2D Imager, Camera
<b>Wireless Communication</b>	Bluetooth® 4.2 + BR/EDR + BLE WLAN WWAN LTE GPS	Bluetooth® WLAN	Bluetooth® WLAN WWAN GPS
<b>Keypad</b>	8-key (2 customizable) + Touchscreen	Touchscreen	Touchscreen
<b>Battery</b>	Li-Ion 8200 mAh (changeable)	Li-Ion 9000 mAh	Li-Ion 10800 mAh
<b>IP Rating</b>	IP67	IP67	IP65
<b>Dimensions</b>	9.5in x 5.9in x 0.7in	10.5in x 7.2in x 0.52in	11.1in x 7.6in x 0.8in
<b>Weight</b>	22 oz.	27.5 oz.	42 oz.
<b>Drop Spec.</b>	4ft	4ft	5ft
<b>Warranty</b>	1-year	1-year	1-year

# Wireless Barcode Scanners



	MS650 & MS652+	MS912+	MS916 & MS926	MS926P	MS925HC	MS340B	MS851B / MS852B	MS840P / MS842P
<b>Scanner</b>	1D CCD / 2D CMOS	1D CCD	1D Laser / 2D Imager	1D Laser / 2D Imager	1D Laser / 2D Imager	1D CCD	1D Laser / 2D Imager	2D Imager
<b>Light Source</b>	Red Laser - Enhanced White LED / 1 Hyper Red 660nm LED	625 nm Visible LED	650 nm Visible LED / 5000K White LED w/ CCT	5000k white LED w/ OOT	3000K CCT white LED	635 nm Visible Red LED	650 nm Visible LED 660 nm Hyper Red	625 nm Visible LED
<b>Wireless Communication</b>	Bluetooth® (Compatible w/ Windows, iOS & Android Devices)	Bluetooth® (Compatible w/ Windows, iOS & Android Devices) *2 MB of Memory	Bluetooth® (Compatible w/ Windows, iOS & Android Devices) *2 MB of Memory	Bluetooth® / Dongle	Bluetooth®	Bluetooth® (Compatible w/ Windows, iOS & Android Devices)	Bluetooth® (Compatible w/ Windows, iOS & Android Devices)	2.4GHz Short-Range Wireless via USB Dongle
<b>Cradle</b>	No / Optional	No	Yes / Optional	Optional	No	Optional	Optional / Yes	Optional
<b>Scan Distance</b>	Up to 7in	Up to 7in	Up to 7in	Up to 7in	-	1.5in – 16in	Up to 19.4in	1.5in – 7.5in
<b>Scan Rate</b>	240 scans/sec	240 scans/sec	104 scans/sec	104 scans/sec 30 scans/sec	60 scans/sec	500 scans/sec	104 scans/sec	60 fps
<b>ESD Protection</b>	-	-	-	-	-	-	-	Yes
<b>Operation Mode</b>	Trigger, Continuous	Trigger, Continuous	Trigger, Continuous, or Presentation	Trigger, Continuous, or Presentation	Trigger, Presentation	Trigger, Continuous	Trigger, Continuous	Trigger, Presentation
<b>Operation Temperature</b>	32°F to 122°F	32°F to 122°F	32°F to 122°F	32°F to 122°F	14°F to 122°F	32°F to 122°F	32°F to 122°F	15°F to 122°F
<b>Storage Temperature</b>	-4°F to 149°F / -4°F to 140°F	-4°F to 158°F	-4°F to 140°F	-4°F to 140°F	-4°F to 140°F	-4°F to 158°F	-4°F to 140°F	-4°F to 140°F
<b>Drop Spec.</b>	5ft	5ft	5ft	5ft	5ft	5ft	6.8ft	6ft
<b>Dimensions</b>	1.8in H x 1.1in W x 1.1in D / 1.9in H x 2.8in W x 0.8in D	2.8in H x 1.2in W x 0.8in D	3.8in H x 1.5in W x 0.8in D	3.8in H x 1.5in W x 0.8in D	1.08in H x 2.6in W x .63in D	2.8in H x 2.8in W x 6.5in D	4.7in H x 3.4in W x 3.3in D	6.9in H x 2.9in W x 3.5in D
<b>Interface</b>	USB	USB	USB	USB	USB	USB	USB	USB
<b>Weight</b>	0.5 oz. / 3.4 oz.	1.1 oz.	2.2 oz.	2.2 oz.	1.04 oz.	6.1 oz.	7.5 oz.	7.3 oz.
<b>Warranty</b>	1-year	1-year	1-year	1-year	1-year	1-year	1-year	1-year

\*The Unitech Protection Plus Warranty Program covers all system devices for a minimum of one year and all cables and batteries for 90 days. Additional prepaid services, such as Extended and Comprehensive Warranty offer coverage for an additional one or two year term.

# Wireless Barcode Scanners

	MS622	MS836B	MS838B	MS851B	MS852B+	MS852BLR
<b>Scanner</b>	2D CMOS Sensor 640 x 480px	1D Laser	1D Laser / 2D Imager CMOS Sensor, 640 x 480px	1D Laser	2D Laser 1280 X 800 global shutter	2D Laser 1280 X 800 global shutter
<b>Light Source</b>	White LED Red LED 625nm	650 nm LED	Color temperature 3500 k 25nm LED	650 nm visible laser diode	White LED	White LED
<b>Wireless Communication</b>	Wired USB-C	Bluetooth® 2.4G USB Dongle *16 MB of Memory	Bluetooth® 2.4G USB Dongle *16 MB of Memory	Bluetooth®	Bluetooth®	Bluetooth®
<b>Cradle</b>	-	Hands-Free Stand	Hands-Free Stand	Yes / Optional	Yes / Optional	Yes / Optional
<b>Scan Distance</b>	Up to 7in	Up to 7in	Up to 7in	Up to 7in	Up to 7in	Up to 68ft
<b>Scan Rate</b>	60 frames/sec	300 scans/sec	60 frames/sec	Up to 104 scans/sec	-	-
<b>ESD Protection</b>	-	-	-	ESD Models Available	ESD Models Available	ESD Models Available
<b>Operation Mode</b>	Trigger Left and Right handed	Trigger or Automatic	Trigger, Presentation, or Buffer	Trigger, Pulse, Flash, Continuous	Trigger, Presentation, or Buffer	Trigger, Presentation, or Buffer
<b>Operation Temperature</b>	4°F to 131°F	14°F to 122°F	14°F to 122°F	14°F to 122°F	14°F to 122°F	14°F to 122°F
<b>Storage Temperature</b>	-40°F to 158°F	-4°F to 140°F	-4°F to 140°F	-40°F to 158°F	-40°F to 158°F	-40°F to 158°F
<b>Drop Spec.</b>	5ft	5ft	5ft	6.8ft	6.8ft	6.8ft
<b>Dimensions</b>	1.08in H x 1.82in W x 1.05in D	6.8in H x 2.8in W x 3.7in D	6.8in H x 2.8in W x 3.7in D	3.4in H x 2.8in W x 6.9in D	4.7in H x 3.4in W x 3.3in D	4.7in H x 3.4in W x 3.3in D
<b>Interface</b>	USB-C	USB	USB	USB	USB, RS232	USB, RS232
<b>Weight</b>	0.5 oz. (without cable)	7.6 oz.	7.1 oz.	7.5 oz.	7.5 oz	7.5 oz
<b>Warranty</b>	1-year	1-year	1-year	1-year	1-year	1-year

# Corded Barcode Scanners



	AS10	MS250	MS282E	MS340	MS836	MS838
<b>Scanner</b>	1D CCD	1D CCD	1D CCD / 2D Imager	1D CCD	1D Laser	1D Laser / 2D Imager
<b>Light Source</b>	632 nm LED	632 nm LED	625 nm LED / Hyper Red 660 nm	635 nm LED	650 nm LED	Red LED / White LED
<b>Scan Distance</b>	Contact	Contact - 3.54in	1.2in - 11.4in	Contact - 15in	Up to 8in	Up to 8in
<b>Scan Rate</b>	100 scans/sec	200 scans/sec	30 frames/sec	500 scans/sec	100 scans/sec	60 frames/sec
<b>ESD Protection</b>	-	-	-	-	-	-
<b>Operation Mode</b>	Trigger	Trigger, Continuous	Trigger, Presentation	Trigger, Presentation	Trigger, Presentation	Trigger, Presentation
<b>Operation Temperature</b>	32° to 122°F	32°F to 122°F	32°F to 122°F	32°F to 122°F	32°F to 113°C	14°F to 122°F
<b>Storage Temperature</b>	-4° to 158°F	-4°F to 158°F	-22°F to 158°F	-4°F to 158°F	-4°F to 140°C	-4°F to 140°F
<b>Drop Spec.</b>	4ft	5ft	5ft	5ft	5ft	5ft
<b>Dimensions</b>	7in H x 2.5in W x 3.2in D	6.4in H x 2.46in W x 3.11in D	7.07in H x 1.87in W x 2.01in D	2.8in H x 2.8in W x 6.5in D	6.2in H x 2.7in W x 3.7in D	6.8in H x 2.8in W x 3.7in D
<b>Interface</b>	Keyboard Wedge, USB	Keyboard Wedge, RS232, USB	USB	Keyboard Wedge, RS232, USB	USB	USB / RS232
<b>Weight</b>	4.2 oz.	2.9 oz.	4.5 oz.	6 oz.	5.3 oz.	5.5 oz.
<b>Warranty</b>	1-year	3-year	3-year	5-year	1-year	1-year

# Corded Barcode Scanners

	MS851	MS852	MS852+	MS852+ LR
<b>Scanner</b>	1D Laser	2D Imager	2D Imager	1D CCD / 2D Imager
<b>Light Source</b>	650 nm LED	660nm Hyper red	660nm Hyper red	660nm Hyper red
<b>Scan Distance</b>	Up to 18in	Up to 19.4in	Up to 19in	Up to 820in
<b>Scan Rate</b>	104 scans/sec	-	-	-
<b>ESD Protection</b>	Yes	-	Yes	-
<b>Operation Mode</b>	Trigger, Continuous	Trigger, Auto sensing, Presentation	Trigger, Presentation, Auto sensing	Trigger, Presentation
<b>Operation Temperature</b>	14°F to 122°F	14°F to 122°F	14°F to 122°F	14°F to 122°F
<b>Storage Temperature</b>	-40°F to 158°F	-40°F to +158°F	-40°F to 158°F	-40°F to 158°F
<b>Drop Spec.</b>	6.8ft	6.8ft	6.8ft	7.8ft
<b>Dimensions</b>	6.9in H x 2.8in W x 3.4in D	6.9in H x 2.8in W x 3.4in D	6.9in H x 2.8in W x 3.4in D	6.9in H x 2.8in W x 3.4in D
<b>Interface</b>	USB	USB	USB	USB
<b>Weight</b>	5.1 oz.	5.1 oz.	5.8 oz.	6.4 oz.
<b>Warranty</b>	1-year	1-year	5-year	1-year





## Pen & Slot Scanners



## Corded Barcode Scanners

## Magnetic Strip Readers

	MS100	MS120	MS146
<b>Reader</b>	1D	1D	1D Visible Light or Infrared Beam
<b>Light Source</b>	650 - 660 nm Red LED	660 nm Red LED	660 nm Visible LED (MS146) 930 nm Infrared LED (MS146I)
<b>Scan Distance</b>	Contact	Contact	Contact
<b>Scan Rate</b>	4in - 24in Per Second	2in - 78in Per Second	2in - 30in Per Second
<b>Operation Mode</b>	Manual	Manual	Manual
<b>Operation Temperature</b>	32°F to 122°F	32°F to 131°F	32° to 122°F
<b>Storage Temperature</b>	-4°F to 140°F	4°F to 158°F	-4° to 140°F
<b>Drop Spec.</b>	5ft	5ft	5ft
<b>Dimensions</b>	5.5in L x 1.2in D	5.8in L x .52in D	3.7in H x 1.3in W x 1.8in D
<b>Interface</b>	TTL, Keyboard Wedge, RS232, USB	TTL, Keyboard Wedge, RS232, AT	TTL, Keyboard Wedge, RS232, USB, AT
<b>Weight</b>	2.7 oz.	2.1 oz.	6.7 oz.
<b>Warranty</b>	2-years	1-year	2-years

	MS246	MSR120
<b>Magnetic Head Life</b>	1 million passes	1 million passes
<b>Magnetic Stripe Formats</b>	ISO 7811, AAMVA	ISO 7811, AAMVA, & CA DMV
<b>Swipe Speed</b>	5 - 50in bi-directional	3in - 55in bi-directional
<b>Card Thickness</b>	.015in - .045in	0.010in - 0.050in
<b>Slot Width</b>	0.50in	0.50in
<b>Indicators</b>	Tri-colored LED, beeper	Tri-colored LED, beeper
<b>Operation Temperature</b>	32°F to 131°F	32°F to 131°F
<b>Storage Temperature</b>	-22°F to 158°F	-22°F to 158°F
<b>Interface</b>	USB	USB

# Barcode Scanners

## Presentation Scanners



	FC75	FC77	TS100
<b>Scanner</b>	2D Imager	1D Imager / 2D Imager	2D Imager
<b>Light Source</b>	625 nm LED	625 nm LED	650 nm LED
<b>Scan Distance</b>	2in - 7.7in	Contact - 3.54in	Contact - 1.5in
<b>Scan Rate</b>	120 scans/sec	120 secs/sec	-
<b>Operation Mode</b>	Continuous	Continuous	Continuous
<b>Operation Temperature</b>	-4° to 144°F	32°F to 104°F	32°F to 122°F
<b>Storage Temperature</b>	-22° to 158°F	-4°F to 140°F	-4°F to 158°F
<b>Drop Spec.</b>	4ft	3ft	-
<b>Dimensions</b>	1.1in H x 2.7in W x 2.2in D	6.4in H x 3.35in W x 3.84in D	4.1in H x 5.7in W x 2.7in D
<b>Interface</b>	USB	USB	USB / RS232
<b>Weight</b>	3 oz.	12.4 oz.	12.1 oz.
<b>Warranty</b>	3-years	3-years	1-year